



Type REEC 3 Phase Reversing Contactors

LIST PRICES

Resistive AC-1	Inductive AC-3	Horse Power Ratings UL 3 Phase Motor		OPEN	NEMA 1 General Purpose (metal)	NEMA4X Hose Dust Tight (non metal)	NEMA 4/12 (metal)	NEMA 3R Hose + Dust Tight Outdoor (metal)	Dimensions mm/inches open style	
		Volts	HP						MM	Inches
25A	12A	200V	3	REEC 12 - * 0 \$90.00	REEC 12 - * 1 \$173.00	REEC 12 - * 4X \$205.00	REEC 12 - * 4 \$230.00	REEC 12 - * 3R \$229.00	H	74/2.91"
		230V	3						W	104/4.09"
		480V	7 1/2						D(AC)	80/3.15"
		600V	10						D(DC)	115/4.53"
32A	18A	200V	5	REEC 18 - * 0 \$111.00	REEC 18 - * 1 \$211.00	REEC 18 - * 4X \$242.00	REEC 18 - * 4 \$263.00	REEC 18 - * 3R \$258.00	H	74/2.91"
		230V	5						W	106/4.17"
		480V	10						D(AC)	85/3.35"
		600V	15						D(DC)	120/4.72"
40A	25A	200V	5	REEC 25 - * 0 \$132.00	REEC 25 - * 1 \$237.00	REEC 25 - * 4X \$276.00	REEC 25 - * 4 \$284.00	REEC 25 - * 3R \$279.00	H	84/3.30"
		230V	7 1/2						W	126/4.96"
		480V	15						D(AC)	93/3.66"
		600V	20						D(DC)	130/5.12"
50A	32A	200V	10	REEC 32 - * 0 \$156.00	REEC 32 - * 1 \$266.00	REEC 32 - * 4X \$317.00	REEC 32 - * 4 \$317.00	REEC 32 - * 3R \$311.00	H	84/3.30"
		230V	10						W	126/4.96"
		480V	20						D(AC)	98/3.86"
		600V	25						D(DC)	135/5.31"
60A	40A	200V	10	REEC 40 - * 0 \$227.00	REEC 40 - * 1 \$375.00	REEC 40 - * 4X \$423.00	REEC 40 - * 4 \$407.00	REEC 40 - * 3R \$391.00	H	127/5.00"
		230V	10						W	165/6.50"
		480V	30						D(AC)	114/4.49"
		600V	30						D(DC)	171/6.73"

*Coil Voltage Suffix

* - Add Suffix	AC Voltage	* - DC Voltage
-A =	120V 50/60Hz	
-C =	208V up to 230V 60Hz	-DCM = 12VDC
-E =	480V 60Hz, 400V 50Hz	-DCN = 24VDC
-F =	600V 60Hz	-DCO = 48VDC
-D =	380V 50Hz	-DCP = 125VDC
-G =	24V 50/60Hz	-DCR = 220VDC
-H =	277V(280) 60Hz	
-B =	220V 50/60Hz	

Contact Factory for additional coil voltages not listed.
208V "c" Coil -5% Voltage Tolerance.

DC Coil Price Adder Size + List Price

EEC 12-32 + \$60
EEC 40-80 + \$120
EEC 115 + No Adder

