


Type LS05
**MINI POWER RELAY
 MINI CONTACTOR**



Type LS07
**MINI POWER RELAY
 MINI CONTACTOR**



Type XLS05
MINI STARTER



MINI CONTACTORS STARTERS POWER RELAYS

POSITIVE GUIDED RELAYS & CONTACTORS

AEG COMPONENT
 CONTROLS

SERIES LS07 SPECIFICATIONS

- ✓ **16 Amp Resistive (UL)**
 AC-1 (16 AMP 600 Volt)
- ✓ **Mechanical Life Operations**
 10,000,000
- ✓ **Maximum HP Ratings**
 3 Phase
 460 Volt 3HP CE

SERIES LS05 SPECIFICATIONS

- ✓ **15 Amp Inductive (UL)**
 AC-1 (20 AMP 600 Volt)
- ✓ **Mechanical Life Operations**
 AC 10,000,000
- ✓ **Maximum HP Ratings**
 3 Phase
 460 Volt 5HP

Connection Options LS07

- Pressure Wire Terminals
- Spade (Plug-On)
- PC Board (pin terminal)

Low Coil Burden 1.2 Watt

Internationally Accepted

- CE, UL, IEC, S +, BS, VDE, CSA

Overload Relay Type B05

- Ambient Temperature Compensated
- Three Pole Plug-on Separate Mount
- Differential Single Phasing Protection

Enclosures

- M1 - General Purpose
- M12 - Dust Tight
- 4X - Non Metal
- Water & Dust Tight



**ELECTRICAL & ELECTRONIC
 CONTROLS, INC.**
 3881 DANBURY ROAD
 BREWSTER, NY 10509
 845-278-5777 FAX 845-278-5444
 E-MAIL: info@eecontrols.com

EE CONTROLS, LTD
 17 STEWART COURT
 ORANGEVILLE, ONTARIO
 CANADA L9W 3Z9
 519-941-6845 FAX 519-940-0514
 E-Mail: infoeecontrols@on.aibn.com